



## 90 MIN WOOD VENEER DOOR CONSTRUCTION SPECS

Prescott Industries 5-Ply Premium Flush Door Construction:

All Prescott Industries Premium Architectural Doors Type PC-5/FD-3 meet or exceed standards set forth by WDMA I.S.1-A and the AWI for PC-5 as tested per A.S.T.M. E-152 by Warnock Hersey International. Prescott Industries is authorized through INTERTEK to construct and mark 90-minute rated fire doors.

Top and Bottom Rails:  
2" Thick Firestop, top and bottom.  
Top rail and bottom rail can be specified to meet specialized hardware requirements

Core Type:  
Incombustible, non-asbestos,  
engineered, mineral core

Crossband:  
1/10" High Density Fiber Crossband

Stiles:  
1" Firestop laminated to 1/2" (before  
trim) wood for stained edges.  
Stiles and special blocking can be  
specified to meet specialized  
hardware requirements.

Faces:  
White Maple, Red Oak, Birch, and more.  
Premium, Grade A wood for wood face.

Adhesives: Meet requirements of WDMA  
I.S.1A, C-6

Door Thickness: 1-3/4"

Maximum Size: 4' x 9'

Warranty: Premium Architectural Doors (Lifetime Warranty)

Note: Interior use only. (Exterior use applications not warranted.)

